## quantum technology, inc.

108 Commerce St., Suite 101, Lake Mary, Florida, 32746-6212, USAFAX 407-333-9352PHONE 407-333-9348TOLL FREE 800-232-4291EMAIL: staff@QuantumTech.comWEB: www.QuantumTech.com

MODEL *POWERMAX HV POWER SUPPLY* DATA SHEET 783

## POWERMAX<sup>TM</sup> INTEGRATED HV POWER SUPPLY

## ✓ 1-9 KV OUTPUT ✓ 30 WATT OUTPUT ✓ FLEXIBLE MOUNTING

The PowerMax Integrated HV Power Supply is useful for powering tall the supply requirements of Quantum HV Pulsers from the HVP-525, 590 series to the New SUNFIRE AND STARFIRE HV switching systems for pockels cells/Q-switches used in Regen Pulse Picker and Cavity Dumper applications. This is an economical OEM type package with HV disable/current limit/remote HV control and DC voltage monitor. The unit is generally conductively cooled running off 24V supply to power the internal HV electronics.

**POWERMAX<sup>™</sup> INTEGRATED HV POWER SUPPLY** Specifications

Models:	POWERMAX-6005 6KV, 5mA
	POWERMAX-9003 9.5KV, 3mA
Voltage Stability:	.02%
Line/Load Regulation:	<0.01%
Voltage monitor into10Mohm:	1V per KV (+/- 2%)
Disable Voltage:	3-24V in >10 Kohm
AuxillaryVoltages:	325 V, Vin
I/O Connector:	5 pin molex plug
HV Output Connector:	SHV
LV Output Connector:	Mini-DIN
Input Power Connector:	2.5 mm power jack
Status Indicator LEDs:	LV main power on HV power on/Shut down
Fault conditions:	Voltage Limit, Current Limit, Thermal Shut down
Input Voltage	24V, 35W (15V on some units)
Size:	4x4x1.5 inches not including I/O pins